

634-2

NOLTR 62-179

409 623

CAT. BY DDC
AS AD No. 109623


NOL

THE DEVELOPMENT OF AN EXPLOSIVE
DRIVEN, SHUTTER-TYPE, HIGH
PRESSURE RELEASE

30 OCTOBER 1962

UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

NOLTR 62-179



UNCLASSIFIED
NOLTR 62-179

Ballistics Research Report 82

THE DEVELOPMENT OF AN EXPLOSIVE DRIVEN,
SHUTTER-TYPE, HIGH PRESSURE RELEASE

Prepared by
Rayner A. Montgomery and E. Eugene Kilmer

ABSTRACT: An investigation was conducted to determine the feasibility of using a shutter-type pressure release for a 1-1/2-inch shock tunnel. This device was operated by an explosive driver producing opening times in the order of 500 microseconds. The shutter mechanism was tested up to 500 psi differential pressure.

PUBLISHED APRIL 1963

U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

NOLTR 62-179

30 October 1962

**THE DEVELOPMENT OF AN EXPLOSIVE DRIVEN, SHUTTER-TYPE
HIGH PRESSURE RELEASE**

This investigation was undertaken as a possible method of hypersonic shock tunnel flow improvement. This work was performed under NOL Task No. 363 by the Ballistics Design and Operations Division of the Ballistics Department with the support of the Explosion Dynamics Division of the Explosions Research Department.

This work was sponsored by the Re-entry Body Section of the Special Projects Office, Bureau of Naval Weapons, under the Applied Research Program in Aeroballistics.

The authors wish to express their appreciation to Mr. Paul Fineran, Mr. William James, Mr. Robert Oetting, and Mr. Paul Cords for their assistance, and to Mr. Martin Wahler for preparation of diagrams.

R. E. ODENING
Captain, USN
Commander

A. E. Seigel
A. E. SEIGEL
By direction

CONTENTS

	Page
INTRODUCTION	1
SHUTTER-TYPE RELEASE	1
EXPLOSIVE DRIVER	2
MONITORING EQUIPMENT	3
RESULTS AND DATA REDUCTION	3
CONCLUSIONS	4

ILLUSTRATIONS

Figure	Page
1 Shutter Assembly (Sectioned)	5
2 Shutter Assembly in Closed and Open Position	6
3 Explosive Driver and Pressure Monitoring Device.	7
4 Shutter Monitoring System	8
5 Typical Pressure Trace from the Explosive Driver in the Shutter Assembly	9
6 High-Speed Photographs of Shutter Opening	10
7 Typical Opening Rate	11
8 High Pressure Release Performance Curve	12

TABLES

Table I High Pressure Release Performance Data	13
--	----

REFERENCES

- (1) Dawson, V. C. D., "Piston-Type Strain Gages,"
NAVORD Report 6251, Jan 1959 (Unclassified)
- (2) Progress Report No. 58, Contract NOrd 13466: Task II,
Armament Division, Universal Match Corporation
(Confidential)

INTRODUCTION

In the hypersonic shock tunnels, it is desirable to eliminate all disturbances which tend to detract from the uniformity of the flow. A reduction in the magnitude of these flow disturbances would improve the reproducibility of the flow in the test section. Presently, metal diaphragms are used at the muzzle end of a straight-through shock tunnel. These diaphragms require a pressure buildup in order to be opened. This tends to reflect the incident shockwave, thus increasing the disturbance in the shock tunnel flow.

The purpose of this investigation was to design and develop a fast-acting valve which would improve flow conditions and reduce costs compared to metal diaphragms. A sliding shutter-type release mechanism was designed and tested. This device was actuated by an explosive driver which was loaded with various amounts of smokeless powder. The functioning of the shutter was observed by using a high-speed camera to record the motion. In the fastest operation, the shutter required 440 microseconds to uncover the 1-1/2-inch diameter bore. It was concluded from the functioning time of the shutter that the valve should be acceptable for evaluation in the 1-1/2-inch shock tunnels.

The following points of interest were studied:

- a. The sliding shutter mechanism - A study was made of the parameters affecting the operation of the sliding shutter including, among others, the mass of the shutter and the maximum force the mechanism would withstand.
- b. The explosive driver - The design of the explosive driver was made to incorporate the fastest functioning time yielding optimum operating conditions for the sliding shutter.
- c. The efficiency of the system - A study was made of the operating parameters from the test data, and the efficiency of the system was determined.

SHUTTER-TYPE RELEASE

This unit was designed so that a shutter slides in a housing across a 1-1/2-inch diameter orifice. The shutter is a rectangular piece of aluminum plate with a 1-1/2-inch diameter hole in it. This shutter is positioned by a recess in the

housing and is moved from closed to open position by an explosive driver. A sectioned view of the assembly is shown in figure 1. A view of the unit in its closed and open positions is shown in figure 2. Taken under consideration, in the design of the shutter unit, were the deflection of the shutter while holding the loading pressure, the shutter mass, and the compressive strength required to withstand the expected acceleration and deceleration without damaging the components.

EXPLOSIVE DRIVER

The explosive driver was designed from the Naval Ordnance Laboratory WOX-10A Explosive Driver. This driver was modified in the following ways:

a. The resistors, which are normally in parallel with the two WOX-26A Actuators, were removed. This was to facilitate the use of a low voltage power supply.

b. The capsule, normally loaded with one gram of Unique Powder, was loaded with various weights of SR 4990 Smokeless Powder. The smokeless powder was chosen because it has a shorter pressure rise time and would therefore be expected to bring about a more rapid shutter motion.

c. The piston was increased from 1.3 inches to 2.6 inches in length to produce the necessary increase in displacement.

d. Allowances were made in the design so that piston over-travel would not affect the operation of the shutter or damage other parts. The sudden stop of the driver piston at the end of its travel produces extremely high forces which may cause deformation.

e. The body was modified to accept the longer piston and also to accept a shear pin. The sectional view of the explosive driver in figure 3 indicates the arrangement of the explosive components and associated parts. The two WOX-26A Explosive Actuators were connected in parallel in the electrical circuit to shorten the inherent delay time of any single actuator and to gain reliability of functioning. The actuators were placed in a manner so that each was directed toward the powder capsule. Several weights of SR 4990 Smokeless Powder were used in the capsules, depending on the tests involved.

MONITORING EQUIPMENT

A block diagram of the test equipment is shown in figure 4. In order to obtain displacement of the shutter with respect to time, a rotating-mirror framing camera was used to observe the movement of the shutter across the 1-1/2-inch diameter orifice. To obtain the force exerted by the explosive driver, a pressure measurement was required. A pressure sensing device (ref. (1)) which produces an electrical signal was adapted, as shown in figure 3. The oscilloscope trace of this signal was recorded on photographic film for the purpose of calculating the system's efficiency.

RESULTS AND DATA REDUCTION

Various weights of smokeless powder were compared in order to determine an optimum base charge in the driver. The efficiency of the system was taken to be the ratio of work done in moving the piston to the energy available in the powder. The work was obtained by measuring the area under the force displacement curve. The energy was taken to be the theoretical impetus (ref. (2)) (foot pounds per pound of propellant). The preliminary test with 1/2-gram capsules of SR 4990 Smokeless Powder showed the efficiency to be about 43 percent, as shown in Table I. It was decided that the shutter could be driven at a greater velocity by increasing the force during the stroke. This was accomplished by allowing an initial pressure buildup through the use of shear pins placed through the driver body and piston rod. A typical trace of the pressure produced by the smokeless powder while pushing the driver piston under the load of the shutter mechanism and the shear pin is shown in figure 5. Several different diameters of shear pins were tried while holding the shutter and piston weight constant (150 grams). The results of six tests, as shown in Table I, indicate that the efficiency could be increased to approximately 80 percent by proper selection of base charge and shear pin diameter. Also, it can be seen that the shutter velocity is increased when a shear pin is used.

A typical sequence of high-speed photographs of the shutter mechanism uncovering a 1-1/2-inch orifice is shown in figure 6. The camera was operated at a speed that would give a 40-microsecond spacing between frames. A plot of the opening characteristics versus time for Test No. 5 is shown in figure 7. In order to obtain a general indication of performance, the values of peak pressure and shutter opening time are plotted in figure 8. These six tests were conducted at 250 psi pressure

NOLTR 62-179

differential. Preliminary tests performed at 500 psi indicate that the shutter will operate satisfactorily in the higher pressure differential.

CONCLUSIONS

During the limited number of tests conducted, this device consistently operated within 640 microseconds. This is considered to be acceptable for evaluation in the 1-1/2-inch diameter shock tunnel.

The best functioning time, as indicated from test performance, was found to be 440 microseconds with 250 psi differential pressure. The explosive driver shutter-type mechanism functioned satisfactorily up to the designed 500 psi differential pressure.

Increased performance and efficiency of this device was obtained by using a holdback technique.

The demonstrated feasibility of this device indicates that the next evaluation should be conducted in a shock tunnel.

The rapid opening time and the smooth continuous opening produced by this mechanism suggests its usefulness in other applications.








FIGURE 1. SHUTTER ASSEMBLY.
(SECTIONED)



SHUTTER CLOSED



SHUTTER OPEN

FIGURE 2. SHUTTER ASSEMBLY IN CLOSED AND OPEN POSITION.




FIGURE 3. EXPLOSIVE DRIVER AND PRESSURE MONITORING DEVICE.





FIGURE 4. SHUTTER MONITORING SYSTEM



TIME : 1 CM. = 500 μ SEC.

PRESSURE : 1 CM. = 2770 P.S.I.

FIGURE 5. TYPICAL PRESSURE TRACE FROM THE EXPLOSIVE DRIVER IN THE SHUTTER ASSEMBLY.

NOLTR 62-179




FIGURE 6. HIGH SPEED PHOTOGRAPHS OF SHUTTER OPENING.




FIGURE 7. TYPICAL OPENING RATE




FIGURE 8. HIGH PRESSURE RELEASE PERFORMANCE CURVE

TABLE I
HIGH PRESSURE RELEASE PERFORMANCE DATA

TEST	1	2	3	4	5	6
Shutter						
Opening Time*	640	600	560	520	520	440
Explosive Driver						
Explosive Weight	0.50	0.50	0.50	0.60	0.60	0.75
Shear Pin Release Pressure	None	3,000	4,000	3,000	3,000	5,000
Maximum Pressure	6,240	10,550	12,200	13,300	13,300	19,950
Efficiency	43	66	**	61	63	80
Work	2213	3371		3694	3852	6089
Impetus	5100	5100		6120	6120	7650
* Shutter time measured from photographs in 40 microsec. increments						
** Poor pressure trace.						

NOLTR 62-179

DISTRIBUTION

	Copies
Chief, Bureau of Naval Weapons Department of the Navy Washington 25, D. C.	
RMMO	1
RMGA	1
RRMA	1
DIS-32	2
RRRE-5	1
RUME-32	1
Director, Special Projects Office Department of the Navy Washington 25, D. C.	
SP-20	4
SP-27	2
SP-272	1
Chief, Bureau of Ships Department of the Navy Washington 25, D. C.	1
Superintendent Naval Post Graduate School Monterey, California	1
Office of Naval Research Room 2709 T-3 Washington 25, D. C. Head, Mechanics Br.	1
Commander U. S. Naval Ordnance Test Station China Lake, California Technical Library	2
Director Naval Research Laboratory Washington 25, D. C. Code 2027 Mr. Edward Chapin, Code 6310	1 1
Director David Taylor Model Basin Washington 7, D. C. Library Weapons Laboratory	1 1

NOLTR 62-179

	Copies
Commander, Naval Air Development Center Johnsville, Pennsylvania	1
Commander U. S. Naval Weapons Laboratory Dahlgren, Virginia Library	1
Commander Pacific Missile Range Point Mugu, California Technical Library	1
Commanding Officer U. S. Naval Weapons Station Yorktown, Virginia R&D Division	2
Commanding Officer U. S. Naval Ordnance Laboratory Corona, California Library	1
Commanding Officer U. S. Naval Propellant Plant Indian Head, Maryland Technical Library	1
EODTC	1
Commanding Officer Office of Naval Research Branch Office, Box 39, Navy 100 Fleet Post Office, New York, N. Y.	5
Office, Chief of Ordnance Department of the Army Washington 25, D. C. ORDTU	1
Commanding General Army Rocket & Missile Agency Redstone Arsenal, Huntsville, Alabama Mr. John Morrow	1
Commanding Officer Picatinny Arsenal Dover, New Jersey ORDBB-TH8	1

Copies

Commanding Officer Diamond Ordnance Fuze Laboratory Connecticut & Van Ness St., N. W. Washington 25, D. C. Library	1
Commanding Officer Office of Ordnance Research Box CM Duke Station Durham, North Carolina	1
Commanding Officer Engineer Research and Development Laboratory U. S. Army Ft. Belvoir, Virginia	1
Commanding General Aberdeen Proving Ground, Md. Technical Information Branch Ballistics Research Laboratories	1 1
Commander Wright Air Development Center Wright-Patterson Air Force Base, Ohio WCOSI-3 WCLSW-5 WCRRD	2 1 3
APGC (PGTRI, Tech. Lib) Eglin Air Force Base, Florida	1
Commanding General Arnold Engineering Development Center Tullahoma, Tennessee Technical Library AEKS	1 5
Office of the Assistant Secretary of Defense (R&D) Room 3 E1041, The Pentagon Washington 25, D. C. Technical Library	1
Research and Development Board Room 3 D1041, The Pentagon Washington 25, D. C. Library	2

NOLTR 62-179

	Copies
Sandia Corporation P. O. Box 969 Livermore, California	1
Sandia Corporation P. O. Box 5400 Albuquerque, New Mexico	1
Institute for Defense Analysis Advanced Research Projects Agency Washington 25, D. C. Mr. W. G. May, General Sciences Branch	1
U. S. Atomic Energy Commission P. O. Box 62 Oak Ridge, Tennessee TRI:NLP:ATD:10-7	1
National Bureau of Standards Washington 25, D. C. Dr. Galen B. Schubauer	1
Aerojet-General Corporation Ordnance Division Downey, California Dr. Louis Zernow Contract NOrd 16881	1
Allegheny Ballistics Laboratory Cumberland, Maryland	1
E. I. duPont deNemours Eastern Laboratories Explosives Department Gibbstown, New Jersey Dr. L. Coursen	1
Lockheed Aircraft Corp. Missiles and Space Div. P. O. Box 504 Sunnyvale, California Dr. L. H. Wilson	1

	Copies
Director of Intelligence Headquarters, USAF Washington 25, D. C. AFOIN-3B	1
Office of Technical Services Department of Commerce Washington 25, D. C.	100
Director Applied Physics Laboratory Johns Hopkins University 8621 Georgia Avenue Silver Spring, Md.	
Tech. Reports Group	2
Dr. D. Fox	1
Dr. Freeman Hill	1
Dr. L. L. Cronvich	1
Librarian	1
Solid Propellant Agency	1
Atomic Energy Commission Engineering Development Branch Division of Reactor Development Headquarters, US AEC Washington 25, D. C.	
Mr. J. M. Simmons	1
Mr. M. J. Whitman	1
Mr. J. Conners	1
Director U. S. Bureau of Mines Division of Explosive Technology 4800 Forbes Street Pittsburgh 13, Pennsylvania	
Dr. R. W. Van Dolah	1
Chief Defense Atomic Support Agency Washington 25, D. C.	
Document Library	1
ASTIA Arlington Hall Station Arlington 12, Virginia TIPDR	10

	Copies
National Aeronautics and Space Adm. 1520 H Street, N. W. Washington, D. C.	5
NASA Lewis Research Center 21000 Brookpart Road Cleveland, Ohio	
Chief, Propulsion Aerodynamics Div.	1
Mr. George Mandel, Chief, Library	2
NASA Ames Research Center Moffett Field, California	
Librarian	1
A. G. Boissevain	1
NASA George C. Marshall Space Flight Center Huntsville, Alabama	
M-S&M-PT (Mr. H. A. Connell)	5
Dr. W. R. Lucas (M-SFM-M)	1
Dr. Ernst Geissler	1
NASA Langley Research Center Langley Field, Virginia	
Librarian	1
C. H. McLellan	1
J. J. Stack	1
Adolf Busemann	1
Rodger W. Peters (Structures Res. Div.)	1
Russell Hopko, PARD	1
NASA High-Speed Flight Station Edwards Field, California	
W. C. Williams	1
University of California Lawrence Radiation Laboratory P. O. Box 808 Livermore, California	
Mr. W. M. Wells, Propulsion Div.	1
Mr. Carl Kline	1
Director Los Alamos Scientific Laboratory P. O. Box 1663 Los Alamos, New Mexico	
Dr. Donald F. McMillian, N-1 Group Leader	1

	Copies
Lockheed Aircraft Corp. Research Laboratory Palo Alto, California W. Griffith	1
Via: BUWEPSREP P. O. Box 504 Sunnyvale, Calif. SpL-314	1
University of Utah Salt Lake City, Utah Dr. Melvin Cook, Explosive Research Group	1
Cornell Aeronautical Laboratory 4455 Genesee Street Buffalo, New York Dr. Gordon Hall	1
Defense Metals Information Center Battelle Memorial Institute- 505 King Avenue Columbus 1, Ohio	1
United Aircraft Corporation Research Laboratories East Hartford 8, Connecticut Mr. H. J. Charette Mr. H. Taylor	1 1
Kaman Aircraft Corporation Nuclear Division Colorado Springs, Colorado Dr. A. P. Bridges	1
Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena 3, California I. R. Kowlan, Chief, Reports Group Dr. L. Jaffee	1 2
General Applied Sciences Laboratories, Inc. Merrick and Stewart Avenues East Meadow, New York Mr. Robert Byrne	1

Copies

Polytechnic Institute of Brooklyn 527 Atlantic Avenue Freeport, New York Dr. Paul A. Libby Via: Commanding Officer Office of Naval Research Branch Office 346 Broadway New York 13, New York	1
Oak Ridge National Laboratory P. O. Box E Oak Ridge, Tennessee Mr. W. D. Manly	1
Aerospace Corporation El Segundo, California Dr. Bi tondo	1
General Electric Research Laboratory 3198 Chestnut Street Philadelphia, Pennsylvania Dr. Leo Steg	1
Stanford Research Institute Poulter Laboratories Menlo Park, California	1
Armour Research Foundation Technology Center Illinois Institute of Technology 10 West 35th Street Chicago 16, Illinois	1
AVCO Manufacturing Corporation Research and Advanced Development Division 201 Lowell Street Wilmington, Massachusetts Mr. J. P. Wamser	1
AVCO Manufacturing Corporation Everett, Massachusetts Dr. Kantrowitz	1
General Electric Company Space Vehicle and Missiles Department 21 South 12th Street Philadelphia, Pennsylvania Dr. J. Stewart Dr. Otto Klima Mr. E. J. Nolan Mr. L. MCCreight	1 1 1 1

	Copies
Ballistic Research Laboratories Aberdeen Proving Ground, Maryland W. K. Rogers, Jr., Chief Transonic Range Facility	1
ARO, Inc. von Karman Gas Dynamics Facility Arnold Engineering Development Center Arnold Air Force Station, Tennessee J. Lukasiewicz, Chief, VKF	1
U. S. Naval Research Laboratory Washington 25, D. C. H. F. Swift, Impact Damage Section	1
McDonnell Aircraft Co. Box 516 St. Louis 66, Mo. Dr. Morey Schimmel Dept. 331	1

CATALOGING INFORMATION FOR LIBRARY USE

BIBLIOGRAPHIC INFORMATION						
	DESCRIPTORS		CODES		DESCRIPTORS	CODES
SOURCE	NOL technical report		NOLTR		Unclassified - 17	UØ17
REPORT NUMBER	62-179		62Ø179			
REPORT DATE	30 Oct. 1962		1Ø62			

SUBJECT ANALYSIS OF REPORT

DESCRIPTORS	CODES	DESCRIPTORS	CODES	DESCRIPTORS	CODES
Shock tube	SHTU	Feasibility	FEAS		
Valve	VALU	Time	TIME		
Diaphragm	DIAP	Photography	PHOT		
Shutter	SHUE	Test	TEST		
Explosive	EXPL	Components	COMO		
Driver	DRIV				
Metal	META				
Flow	FLOW				
Hypersonic	HYPR				
High pressure	HIGP				
Release	RELE				
Pressure	PRES				

<p>Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 62-179) THE DEVELOPMENT OF AN EXPLOSIVE DRIVEN, SHUTTER-TYPE, HIGH PRESSURE RELEASE (U), by Rayner A. Montgomery and E. Eugene Kilmer, 30 Oct. 1962. 13p. illus., diagr., tables. (Ballistics research report 82) Task 363. UNCLASSIFIED</p> <p>An investigation was conducted to determine the feasibility of using a shutter-type pressure release for a 1-1/2-inch shock tunnel. This device was operated by an explosive driver producing opening times in the order of 500 microseconds. The shutter mechanism was tested up to 500 psi differential pressure.</p> <p>Abstract card is unclassified.</p>	<ol style="list-style-type: none"> Shock tubes - Flow Shock tubes - Diaphragms Shock tubes - Valves Shock tubes - Equipment Title Montgomery, Rayner A. Kilmer, E. Eugene, jt. author Series Project
<p>Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 62-179) THE DEVELOPMENT OF AN EXPLOSIVE DRIVEN, SHUTTER-TYPE, HIGH PRESSURE RELEASE (U), by Rayner A. Montgomery and E. Eugene Kilmer, 30 Oct. 1962. 13p. illus., diagr., tables. (Ballistics research report 82) Task 363. UNCLASSIFIED</p> <p>An investigation was conducted to determine the feasibility of using a shutter-type pressure release for a 1-1/2-inch shock tunnel. This device was operated by an explosive driver producing opening times in the order of 500 microseconds. The shutter mechanism was tested up to 500 psi differential pressure.</p> <p>Abstract card is unclassified.</p>	<ol style="list-style-type: none"> Shock tubes - Flow Shock tubes - Diaphragms Shock tubes - Valves Shock tubes - Equipment Title Montgomery, Rayner A. Kilmer, E. Eugene, jt. author Series Project
<p>Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 62-179) THE DEVELOPMENT OF AN EXPLOSIVE DRIVEN, SHUTTER-TYPE, HIGH PRESSURE RELEASE (U), by Rayner A. Montgomery and E. Eugene Kilmer, 30 Oct. 1962. 13p. illus., diagr., tables. (Ballistics research report 82) Task 363. UNCLASSIFIED</p> <p>An investigation was conducted to determine the feasibility of using a shutter-type pressure release for a 1-1/2-inch shock tunnel. This device was operated by an explosive driver producing opening times in the order of 500 microseconds. The shutter mechanism was tested up to 500 psi differential pressure.</p> <p>Abstract card is unclassified.</p>	<ol style="list-style-type: none"> Shock tubes - Flow Shock tubes - Diaphragms Shock tubes - Valves Shock tubes - Equipment Title Montgomery, Rayner A. Kilmer, E. Eugene, jt. author Series Project